

NAME

`pollrcvd` – *HylaFAX* script for delivering facsimile received by polling

SYNOPSIS

`/var/spool/hylafax/bin/pollrcvd mailaddr faxfile devid commid error-msg`

DESCRIPTION

bin/pollrcvd is the command script invoked by the *HylaFAX* server whenever a facsimile is received as a result of a polling operation. The default script uses electronic mail to deliver the facsimile to the user that submitted the poll request, and can be controlled by editing the **etc/PollDispatch** shell script in the spooling area that is sourced by `pollrcvd` when it runs. The arguments are:

mailaddr the electronic mail address of the user that submitted the poll request.

faxfile the pathname of the received TIFF file relative to the root of the spooling hierarchy.

commid The communication identifier associated with the call (used to include a transcript when an error occurs).

devid the modem device on which the document was received.

error-msg an error message that is non-null if an error was encountered during the receive operation.

NOTES

The default script delivers facsimile as PostScript wrapped in MIME.

FILES

<code>/var/spool/hylafax</code>	spooling area
<code>/usr/local/sbin/faxinfo</code>	for printing information about the facsimile
<code>/usr/bin/fax2ps</code>	for converting TIFF to PostScript
<code>/usr/sbin/sendmail</code>	for delivering mail

SEE ALSO

faxq(8C), *hylafax-server(5F)*, *rcvq(5F)*